




JILONG  
Since 1996

# VFL-22M


## Mini Visual Fault Locator



Mini size



2.5mm Universal  
connector



USB charging



LED light



### Features Description

- ◀ Pocket size
- ◀ Silicone dust cap
- ◀ Measuring up to 30km, high stability
- ◀ 2.5mm Universal adaptor for FC/ SC/ ST
- ◀ With LED lights for dark environment
- ◀ Strong light source, strong penetrating power
- ◀ Lithium battery USB-charging / AA Batteries (optional)

# Product Features



## LED light

Convenient for dark environment



## USB charging

Charging anytime, safe and stable



## Hidden button

Prevent accidental touch



## Measuring up to 30km



High stability



## 2.5mm Universal Connector



SC



ST



FC



## Product Parameters

Model	VFL-22M-10	VFL-22M-20	VFL-22M-30
Output power	10mW	20mW	30mW
Detection distance	8-10km	15-20km	25-30km
Operating hours	Battery	12H	10H
	Rechargeable		4H
Wavelength	650nm		
Laser type	LD		
Modulation frequency	CW / 2Hz		
Operating temperature	-20 ~ +60 (°C)		
LED	Support		
Power	AAA 1.5V batteries x 2 / Lithium battery 1000mAh		
Charging port	USB (only for charging models)		
Dimensions	120 x 35 x 20 (mm)		
Weight	50 g (Including batteries)		

The above data were obtained by Jilong Laboratory in 20°C



## Product Display



## Contact us

### Nanjing Jilong Optical Communication Co., Ltd

Address: 12F, Changfeng Technology Building 2, NO.14 Xinghuo Rd, Pukou District Nanjing City 210032, China

Tel: 025-85880035

Mail: sales@jilongtx.com

Web: www.JILONGOT.com



Focus on official website for more